

A2 Multitrac PEK

Universal Welding Tractor for SAW



A2 Multitrac is a compact versatile tractor suitable for both butt and fillet welds with extremely fast change over time.

Features:

- Choose single or twin wire
- The feed unit secures an even, stable wire feed speed
- Four-wheel drive ensures accurate travel speed
- Digital control panel allows exact pre-set and control of welding parameters
- A2 Multitrac is fully mobile and can easily be moved from one welding station to another
- Can be quickly set-up for different workpieces designed for use with ESAB LAF (DC), TAF (AC), and ARISTO® 1000 AC/DC welding power sources



Ordering Information

A2 Multitrac PEK, SAW 0461233880
 A2 Multitrac PEK, SAW Twin 0461233881

Options & Accessories

Guide wheel bogie 0413542880
 Idling roller (2 per tractor) 0333164880
 V-wheeltrack in steel (set of 4) 0443682881
 Laser lamp kit 0821440980
 Wire reel, plastic, 66 lbs. (30 kg) 0153872880
 Wire reel, steel, 66 lbs. (30 kg) 34323
 Flux recovery unit OPC 0148140880

Specifications

A2 Multitrac PEK	Single SAW	Twin SAW
Wire diameters, in. (mm)		
Steel	1/16-5/32 (1.6-4.0)	2x0.45x3/32 (2x1.2-2.5)
Stainless steel	1/16-5/32 (1.6-4.0)	2x0.45x3/32 (2x1.2-2.5)
Cored wire	1/16-5/32 (1.6-4.0)	-
Aluminum	-	-
Max wire feed speed, ipm (m/min)	354 (9)	354 (9)
Wire reel weight, lbs. (kg)		2x33 (2x15)
Flux hopper capacity, gal. (L)	1.4 (6)	1.4 (6)
Permissible load 100%, A	800	800
Control voltage, V AC	42	42
Travel speed, ipm(m/min)	4-67 (0.1-1.7)	4-67 (0.1-1.7)
Linear slides stroke length, in. (mm)	3.5 (90)	3.5 (90)
Rotary slide setting angle	360°	360°
Weight, excl wire and flux, lbs. (kg)	104 (47)	104 (47)



ESAB / esab.com

