Tel: 01246 205267



HIRE • SALES • REPAIR • REFURBISH









TECHNICAL DATA	WELDMAKER 500CC/CV
WELDING OUTPUT	CC Mode: 40 to 500 amps DC CV Mode: 14 – 37 Volts DC
AUXILIARY OUTPUT	3 Phase 415V AC 50Hz 15kVA 20.8amp 1 Phase 110V AC 50Hz 3kVA 1 x 32amp & 2 x 16amp output receptacles
AVERAGE SOUND PRESSURE LEVEL	71 dB(A) @ 7metres
ENGINE TYPE	EU Stage IIIA Kubota V1505 four cylinder water cooled diesel engine with electric start
FUEL TANK CAPACITY	45 litre
FUEL CONSUMPTION	3.79 litres per hour
RUNNING TIME	Up to 12 hours
DIMENSIONS mm (SKID MOUNTED)	L 1540 x W 720 x H 885
WET WEIGHT (SKID MOUNTED)	578kg
DIMENSIONS mm (ROAD TOW TRAILER)	L 2535 x W 1260 x H 1245
WET WEIGHT (ROAD TWO TRAILER)	647kg

OPTIONAL SPECIFICATIONS:

PETROCHEMICAL

Spark arrestor

Chalwyn valve

OFFSHORE
Spark arrestor
Chalwyn valve
Drip tray
Fuel water trap
Emergency stop button
Anti-static fan belt
Braided fuel lines
Battery isolator switch
Fuel isolator shut off valve

OPTIONAL EXTRAS:

Road towable trailer Welding cables Wire feed unit Remote control Tig HF box with slope in / slope out



Spectrum Welding Supplies Ltd. Spectrum House, McGregor's Way, Chesterfield, Derbyshire, S40 2WB

T 01246 205267 E info@spectrumweldingsupplies.co.uk
W www.spectrumweldingsupplies.co.uk