



SPECTRUM CR 5 TONNE CAPACITY TWIN-DRIVE CYLINDER WELDING ROTATORS



SPECIFICATIONS:

- 1 **MODEL:** SWS-CR5T
- 2 **CAPACITY PER SET (LOADING):** 5000kg
- 3 **CAPACITY PER DRIVE (LOADING):** 2500kg
- 4 **CAPACITY PER IDLER (LOADING):** 2500kg
- 5 **DRIVE TURNING CAPACITY:** 7500kg (when used with 2+ idlers balanced load on even surface)
- 6 **VESSEL SIZE (MIN):** 150mm / 240mm at 70° (cylinder point of contact to tyre)
- 7 **VESSEL SIZE (MAX):** 2500mm at 43°
- 8 **TYRE SIZE:** 300mm x 100mm
- 9 **TYRE MATERIAL:** Polyurethane
- 10 **ELECTRICAL PANEL:** Mounted on drive unit
- 11 **ROLLER SPEED:** 190mm to 1900mm/min at 5 to 50Hz
- 12 **SUPPLY:** 415V-3P-50Hz (10amps) 32amp 5-pin plug fitted (or unless otherwise specified)
- 13 **CONTROL VOLTAGE:** 24V AC
- 14 **DRIVE CONTROL:** 1.1 KW AC Inverter
- 15 **CONTROLLER:** Push button pendant controller (forward / reverse / stop / speed) c/w 10m cable
- 16 **SINGLE-DRIVE MOTOR:** 2x 0.55kw c/w force cooling
- 17 **COOLING FAN SUPPLY:** 240V-1P-50Hz
- 18 **SURFACE PREPARATION:** Grit blast to SA2.5
- 19 **PAINT:** Spray paint
- 20 **COLOUR:** RAL 3003 Red

Spectrum Welding Supplies Ltd. Spectrum House, McGregor's Way, Chesterfield, Derbyshire, S40 2WB

T 01246 205267 E info@spectrumweldingsupplies.co.uk
W www.spectrumweldingsupplies.co.uk

Registered Office: Spectrum House, McGregor's Way, Chesterfield, Derbyshire, S40 2WB
Registered in England and Wales Company Registration No. 1732286
Vat Registration No. 401 5037 11

HIRE • SALES • REPAIR • REFURBISH



- 21 **DRIVE / IDLER WIDTH:** 550 / 266mm
- 22 **DRIVE / IDLER HEIGHT:** 546 / 456mm
- 23 **DRIVE / IDLER LENGTH:** 1690mm
- 24 **DRIVE / IDLER WEIGHT:** 390KG / 270KG

Best regards.



Joe Fitzpatrick BA (Hons)
Managing Director

Tel: 01246 205267
Mobile: 07525 101466
Email: joe@spectrumweldingsupplies.co.uk

